

H.T.H.P LUBRICANTS

Tropicalised High Performance Oil

0W20

Huile moteur moderne, synthétique et économe en carburant, composée d'huiles de base synthétiques spécialement sélectionnées avec un indice de viscosité élevé, auxquelles des additifs avancés sont ajoutés pour obtenir les caractéristiques suivantes:- économie de carburant

- indice de viscosité élevé et très stable
- haute résistance au cisaillement
- démarrage à froid en douceur
- très haute résistance à l'oxydation
- film lubrifiant sûr à des températures de fonctionnement très élevées
- très bonnes propriétés détergentes et dispersantes
- très hautes propriétés anti-usure, anti-corrosion et anti-moussage.

CANDIDATURE

Une huile moteur synthétique spécialement formulée pour économiser du carburant, adaptée aux moteurs à essence des voitures particulières, qui prescrit une huile conforme à la spécification GM dexos1 Ö Gen 2.

SPÉCIFICATION

- API SP Resource Conserving
- ILSAC GF-6A
- Meets the requirements of:
- GM dexos1 (TM) Gen 2
- Chrysler MS 6395
- Ford WSS-M2C947-A/B1 / WSS-M2C962-A1



ANALYSIS

Density at 15°C	0.843
Viscosity at -35°C, mPa.s	4940
Viscosity at 100°C . mm2/s	8.60
Viscosity index	178
Flash point COC, °C	222
Flow point, °C	-36
Alkalinity mgKOH/g	8.5
Sulfate, %	0.89

EXPORT (20FT CONTAINER)

1L	16500 pcs	
5L	3360 pcs	
25L	850 pcs	
205L	98 pcs	

Ensures your engine protection to 100%

www.HTHP.be

Made in Belgium

datasheet 022016v1